

---

# **Python MySQL Replication Documentation**

*Release 0.18*

**Julien Duponchelle**

**Oct 14, 2018**



---

## Contents

---

<b>1</b>	<b>Use cases</b>	<b>3</b>
<b>2</b>	<b>Contents</b>	<b>5</b>
2.1	Installation . . . . .	5
2.2	Limitations . . . . .	5
2.3	BinLogStreamReader . . . . .	6
2.4	Events . . . . .	6
2.5	Examples . . . . .	8
2.6	Support . . . . .	8
2.7	Developement . . . . .	8
2.8	Licence . . . . .	9
<b>3</b>	<b>Indices and tables</b>	<b>11</b>
	<b>Python Module Index</b>	<b>13</b>



Pure Python Implementation of MySQL replication protocol build on top of PyMYSQL. This allow you to receive event like insert, update, delete with their datas and raw SQL queries.



# CHAPTER 1

---

## Use cases

---

- MySQL to NoSQL database replication
- MySQL to search engine replication
- Invalidate cache when something change in database
- Audit
- Real time analytics





## 2.1 Installation

Python MySQL Replication is available on PyPi. You can install it with:

```
pip install mysql-replication
```

## 2.2 Limitations

### 2.2.1 GEOMETRY

GEOMETRY field is not decoded you will get the raw data.

### 2.2.2 binlog\_row\_image

Only [binlog\_row\_image=full]([http://dev.mysql.com/doc/refman/5.6/en/replication-options-binary-log.html#sysvar\\_binlog\\_row\\_image](http://dev.mysql.com/doc/refman/5.6/en/replication-options-binary-log.html#sysvar_binlog_row_image)) is supported (it's the default value).

### 2.2.3 BOOLEAN and BOOL

Boolean is returned as TINYINT(1) because it's the reality.

<http://dev.mysql.com/doc/refman/5.6/en/numeric-type-overview.html>

Our discussion about it: <https://github.com/noplay/python-mysql-replication/pull/16>

## 2.3 BinLogStreamReader

```
class pymysqlreplication.binlogstream.BinLogStreamReader (connection_settings,  
                                                    server_id,  
                                                    ctl_connection_settings=None,  
                                                    resume_stream=False,  
                                                    blocking=False,  
                                                    only_events=None,  
                                                    log_file=None,  
                                                    log_pos=None,           fil-  
                                                    ter_non_implemented_events=True,  
                                                    ignored_events=None,  
                                                    auto_position=None,  
                                                    only_tables=None,   ig-  
                                                    nored_tables=None,  
                                                    only_schemas=None,  
                                                    ignored_schemas=None,  
                                                    freeze_schema=False,  
                                                    skip_to_timestamp=None,  
                                                    report_slave=None,  
                                                    slave_uuid=None,  
                                                    pymysql_wrapper=None,  
                                                    fail_on_table_metadata_unavailable=False,  
                                                    slave_heartbeat=None)
```

Connect to replication stream and read event

```
class pymysqlreplication.binlogstream.ReportSlave (value)  
    Represent the values that you may report when connecting as a slave to a master. SHOW SLAVE HOSTS related
```

```
    encoded (server_id, master_id=0)  
        server_id: the slave server-id master_id: usually 0. Appears as “master id” in SHOW SLAVE HOSTS  
        on the master. Unknown what else it impacts.
```

## 2.4 Events

```
class pymysqlreplication.event.BeginLoadQueryEvent (from_packet,   event_size,   ta-  
                                                    ble_map,           ctl_connection,  
                                                    **kwargs)
```

**Attributes:** *file\_id* block-data

```
class pymysqlreplication.event.ExecuteLoadQueryEvent (from_packet, event_size, ta-  
                                                    ble_map,           ctl_connection,  
                                                    **kwargs)
```

**Attributes:** *slave\_proxy\_id* *execution\_time* *schema\_length* *error\_code* *status\_vars\_length*  
*file\_id* *start\_pos* *end\_pos* *dup\_handling\_flags*

```
class pymysqlreplication.event.GtidEvent (from_packet,           event_size,           table_map,  
                                                    ctl_connection, **kwargs)
```

GTID change in binlog event

**gtid**

GTID = source\_id:transaction\_id Eg: 3E11FA47-71CA-11E1-9E33-C80AA9429562:23 See: <http://dev.mysql.com/doc/refman/5.6/en/replication-gtids-concepts.html>

**class** pymysqlreplication.event.**HeartbeatLogEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

A Heartbeat event Heartbeats are sent by the master only if there are no unsent events in the binary log file for a period longer than the interval defined by MASTER\_HEARTBEAT\_PERIOD connection setting.

A mysql server will also play those to the slave for each skipped events in the log. I (baloo) believe the intention is to make the slave bump its position so that if a disconnection occurs, the slave only reconnects from the last skipped position (see Binlog\_sender::send\_events in sql/rpl\_binlog\_sender.cc). That makes 106 bytes of data for skipped event in the binlog. *this is also the case with GTID replication*. To mitigate such behavior, you are expected to keep the binlog small (see max\_binlog\_size, defaults to 1G). In any case, the timestamp is 0 (as in 1970-01-01T00:00:00).

**Attributes:** ident: Name of the current binlog

**class** pymysqlreplication.event.**IntvarEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

**Attributes:** type value

**class** pymysqlreplication.event.**QueryEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

This event is triggered when a query is run on the database. Only replicated queries are logged.

**class** pymysqlreplication.event.**RotateEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

Change MySQL bin log file

**Attributes:** position: Position inside next binlog next\_binlog: Name of next binlog file

**class** pymysqlreplication.event.**XidEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

A COMMIT event

**Attributes:** xid: Transaction ID for 2PC

## 2.4.1 Row events

These events are sent by MySQL when data are modified.

**class** pymysqlreplication.row\_event.**DeleteRowsEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

This event is triggered when a row in the database is removed

For each row you have a hash with a single key: values which contain the data of the removed line.

**class** pymysqlreplication.row\_event.**TableMapEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

This event describes the structure of a table. It's sent before a change happens on a table. An end user of the lib should have no usage of this

**class** pymysqlreplication.row\_event.**UpdateRowsEvent** (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

This event is triggered when a row in the database is changed

**For each row you got a hash with two keys:**

- `before_values`
- `after_values`

Depending of your MySQL configuration the hash can contains the full row or only the changes: [http://dev.mysql.com/doc/refman/5.6/en/replication-options-binary-log.html#sysvar\\_binlog\\_row\\_image](http://dev.mysql.com/doc/refman/5.6/en/replication-options-binary-log.html#sysvar_binlog_row_image)

**class** `pymysqlreplication.row_event.WriteRowsEvent` (*from\_packet, event\_size, table\_map, ctl\_connection, \*\*kwargs*)

This event is triggered when a row in database is added

For each row you have a hash with a single key: values which contain the data of the new line.

## 2.5 Examples

You can found a list of working examples here: <https://github.com/noplay/python-mysql-replication/tree/master/examples>

### 2.5.1 Prerequisites

The user, you plan to use for the BinaryLogClient, must have REPLICATION SLAVE privilege. To get binlog filename and position, he must be granted at least one of REPLICATION CLIENT or SUPER as well. To get table info of mysql server, he also need SELECT privilege on information\_schema.COLUMNS. We suggest grant below privileges to the user:

```
GRANT REPLICATION SLAVE, REPLICATION CLIENT, SELECT ON *.* TO 'user'@'host'
```

## 2.6 Support

You can get support and discuss about new features on: <https://groups.google.com/d/forum/python-mysql-replication>

You can browse and report issues on: <https://github.com/noplay/python-mysql-replication/issues>

## 2.7 Development

### 2.7.1 Contributions

You can report issues and contribute to the project on: <https://github.com/noplay/python-mysql-replication>

The standard way to contribute code to the project is to fork the Github project and open a pull request with your changes: <https://github.com/noplay/python-mysql-replication>

Don't hesitate to open an issue with what you want to changes if you want to discuss about it before coding.

### 2.7.2 Tests

When it's possible we have an unit test.

`pymysqlreplication/tests/` contains the test suite. The test suite use the standard `unittest` Python module.

**Be careful** tests will reset the binary log of your MySQL server.

Make sure you have the following configuration set in your mysql config file (usually `my.cnf` on development env):

```
log-bin=mysql-bin
server-id=1
binlog-format = row #Very important if you want to receive write, update and_
↳delete row events
gtid_mode=ON
log-slave_updates=true
enforce_gtid_consistency
```

Run tests with

```
py.test -k "not test_no_trailing_rotate_event"
```

This will skip the `test_no_trailing_rotate_event` which requires that the user running the test have permission to alter the binary log files.

Running mysql in docker (main):

```
docker run --name python-mysql-replication-tests -e MYSQL_ALLOW_EMPTY_PASSWORD=true -
↳p 3306:3306 --rm percona:latest --log-bin=mysql-bin.log --server-id 1 --binlog-
↳format=row --gtid_mode=on --enforce-gtid-consistency=on --log_slave_updates
```

Running mysql in docker (for ctl server):

```
docker run --name python-mysql-replication-tests-ctl --expose=3307 -e MYSQL_ALLOW_
↳EMPTY_PASSWORD=true -p 3307:3307 --rm percona:latest --log-bin=mysql-bin.log --
↳server-id 1 --binlog-format=row --gtid_mode=on --enforce-gtid-consistency=on --log_
↳slave_updates -P 3307
```

Each pull request is tested on Travis CI: <https://travis-ci.org/noplay/python-mysql-replication>

## 2.7.3 Build the documentation

The documentation is available in docs folder. You can build it using Sphinx:

```
cd docs
pip install sphinx
make html
```

## 2.8 Licence

Copyright 2012-2014 Julien Duponchelle

Licensed under the Apache License, Version 2.0 (the “License”); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an “AS IS” BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.



## CHAPTER 3

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`





**p**

`pymysqlreplication.binlogstream`, 6  
`pymysqlreplication.event`, 6  
`pymysqlreplication.row_event`, 7



## B

BeginLoadQueryEvent (class in pymysqlreplication.event), 6

BinLogStreamReader (class in pymysqlreplication.binlogstream), 6

## D

DeleteRowsEvent (class in pymysqlreplication.row\_event), 7

## E

encoded() (pymysqlreplication.binlogstream.ReportSlave method), 6

ExecuteLoadQueryEvent (class in pymysqlreplication.event), 6

## G

gtid (pymysqlreplication.event.GtidEvent attribute), 6

GtidEvent (class in pymysqlreplication.event), 6

## H

HeartbeatLogEvent (class in pymysqlreplication.event), 7

## I

IntvarEvent (class in pymysqlreplication.event), 7

## P

pymysqlreplication.binlogstream (module), 6

pymysqlreplication.event (module), 6

pymysqlreplication.row\_event (module), 7

## Q

QueryEvent (class in pymysqlreplication.event), 7

## R

ReportSlave (class in pymysqlreplication.binlogstream), 6

RotateEvent (class in pymysqlreplication.event), 7

## T

TableMapEvent (class in pymysqlreplication.row\_event), 7

## U

UpdateRowsEvent (class in pymysqlreplication.row\_event), 7

## W

WriteRowsEvent (class in pymysqlreplication.row\_event), 8

## X

XidEvent (class in pymysqlreplication.event), 7